

# **NEWTECH 2020**

# **BOOKLET**

**The 6<sup>th</sup> International Conference on**  
*Advanced Manufacturing Engineering and Technologies*

**September 09-11, 2020**  
**Galati, Romania - Online edition**

## Content

Preface .....	3
Conference Committees.....	5
Reviewers List .....	7
Partners .....	8
Plenary Lectures.....	10
Instructions for the chairpersons .....	17
Instructions for oral presentations.....	18
Program of Plenary Lectures.....	19
Program of Oral Presentation.....	21
Abstracts .....	25
Participants Index .....	41

## **PREFACE**

The 6th International Scientific Conference: NEWTECH 2020 – Advanced Manufacturing Engineering and Technologies was organized by Dunarea de Jos University of Galati, Romania. It was held between 9<sup>th</sup>-11<sup>th</sup> of September 2020 in Galati, Romania and was supported by the The Executive Unit for Financing Higher Education, Research, Development and Innovation (UEFISCDI).

The situation with COVID-19 imposed restrictions on holding mass events and travelling. The health of the participants is key and so, the organizing committee, encouraged by the eagerness of the participants to share their scientific work despite the circumstances, decided to hold the conference online.

The 6th International Scientific Conference: NEWTECH 2020 – Advanced Manufacturing Engineering and Technologies provides a forum where recent advances and future directions in the manufacturing processes and forming are discussed by scientists and engineers from academia and industry worldwide. The topics covered are of great interest for academics and for professionals (engineers and researchers) from industry involved in traditional and novel forming and manufacturing technologies for conventional and emerging materials.

The 6th International Scientific Conference: NEWTECH 2020 – Advanced Manufacturing Engineering and Technologies takes place in the year in which the Manufacturing Engineering Department from Faculty of Engineering, Dunarea de Jos University of Galati, Romania, celebrates 60 years of existence.

A total of 40 oral presentations from 10 worldwide countries, Algeria, Cech Republic, France, Greece, Portugal, Serbia, Spain, Romania, Russia, and United States of America are registered including:

- 10 plenary lectures given by renowned experts from academia;
- 30 oral presentations organized in 4 general sessions.

The 30 oral presentations are composed of 30 peer-reviewed full papers (between 6 and 14 pages each one).

All the papers have been reviewed by two expert referees in their relevant fields. The papers selected for the volume depended on their quality and relevancy to the conference.

Free access to all these 30 papers will be granted to all the registered attendees. However, the 30 peer-reviewed full papers and a part of the plenary lectures will be published after the conference, in the open access proceedings by IOP's Conference Series journals, IOP Conference Series: Materials Science and Engineering (<https://iopscience.iop.org/journal/1757-899X>).

In the proceedings, the first section contains a part of the 10 plenary lectures papers delivered by the renowned scientists. These experts were invited to highlight various topics of the conference so as to provide a perspective on the future of scientific and industrial challenges within the scope of the conference. The second section consists of oral presentations which cover Cutting, Milling,

Metrology, Bulk Forming, Hydroforming, Mechanical behaviour, Process Control and Welding. The authors report advances in aspects such as numerical techniques, including artificial intelligence.

The sessions took the form of video conferences, with the scientific community showing great interest all throughout. More than 80 researchers took part online. Each of the authors used Microsoft Teams to present their report, after which the participants in the forum were given the opportunity for discussions.

The main goal of NEWTECH 2020, under the given conditions, was successfully achieved - to bring together researchers from academia and industry, scientists and experts in engineering and technology to address new challenges, share solutions and discuss future research directions.

We would like to thank all those researchers who have trusted the conference and who recognized NEWTECH 2020 as an appropriate forum to share their recent developments and learn about the new trends in the field of technical sciences and engineering.

We thank all the authors for their contribution to this valuable volume. We must also thank all the reviewers for their effort, which ensured not only excellent feedbacks for the authors but also a high-quality scientific research.

Last but not least, we sincerely thank the whole team involved in organizing the NEWTECH 2020 conference.

For the local organizing committee of NEWTECH 2020

V. Paunoiu (UDJG), Chairman

N. Baroiu (UDJG),

V. Teodor (UDJG).



## CONFERENCE COMMITTEES

### Conference Chairman

Professor V. PĂUNOIU (Romania)

### Steering Committee

Professor M. PÍŠKA (Czech Republic)

Professor C. NICOLESCU (Sweden)

Professor A. ARCHENTI (Sweden)

Professor J. JEDRZEJEWSKI (Poland)

Professor W. GRZESIK (Poland)

Professor V. MAJSTOROVIC (Serbia)

### Scientific Committee

Professor S. ADJERID (Algeria)

Professor P. ARRAZOLA (Spain)

Professor D. BANABIC (Romania)

Associate Professor N. BAROIU (Romania)

Professor M. BANU (USA)

Professor N. BÂLC (Romania)

Professor O. BOLOGA (Romania)

Professor I. BONDREA (Romania)

Professor D. BRABAZON (Ireland)

Professor GHE. BRABIE (Romania)

Professor S. CHIKH (Algeria)

Professor M. CACHO (Spain)

Professor R. ČEP (Czech Republic)

Professor S. CHATTI (Tunisie)

Associate Professor B. CHIRITA (Romania)

Professor M. CHOUCANE (Tunisie)

Professor G. CONSTANTIN (Romania)

Professor C. CROITORU (Romania)

Professor J. P. DAVIM (Portugal)

Professor C. DOICIN (Romania)

Professor A. EPUREANU (Romania)

Professor C. FETECANU (Romania)

Professor P. FRANCO (Spain)

Professor G. R. FRUMUSANU (Romania)

Associate Professor A. GAVRUS (France)

Professor M. GHEORGHE (Romania)

Associate Professor GHE. GURAU (Romania)

Professor T. HAMA (Japan)

Professor H. HOCHENG (Taiwan)

Professor M. IORDACHE (Romania)

Professor M. IWANIEC (Poland)

Professor Ž. JAKOVLJEVIĆ (Serbia)

Professor K. JEMIELNIAK (Poland)

Professor S. KARTUNOV (Bulgaria)

Professor R. KHELIF (Algeria)

Professor Y. KORKOLIS (USA)  
Professor P. KYRATSIS (Greece)  
Professor L. N. LÓPEZ DE LACALLE (Spain)  
Professor C. MAIER (Romania)  
Professor S. MEZIANI (Algeria)  
Professor C. MIRONEASA (Romania)  
Professor M. MITREA (Romania)  
Professor F. MZALI (Tunisie)  
Professor D. NEDELCU (Romania)  
Professor J. NI (USA)  
Professor E. NITU (Romania)  
Professor GHE. OANCEA (Romania)  
Professor N. OANCEA (Romania)  
Professor V. PĂUNOIU (Romania)  
Professor H. PEREZ (Spain)  
Professor G. RACZ (Romania)  
Professor S. RADZEVICH (USA)  
Professor J. RECH (France)  
Professor D. RODRIGUES (Portugal)  
Professor A. ROSOCHOWSKI (England)  
Professor F.J. SANTOS MARTIN (Spain)  
Professor T. SAVU (Romania)  
Professor C. SCHNAKOVSKY (Romania)  
Professor E. SCUTELNICU (Romania)  
Associate Professor M.D. STANCIU (Romania)  
Professor V. G. TEODOR (Romania)  
Professor M. TRAJANOVIC (Serbia)  
Professor N. VAXEVANIDIS (Greece)  
Professor I. VOICULESCU (Romania)  
Professor Đ. VUKELIĆ (Serbia)  
Professor H. B. YILDIZ (Turkey)

### Organizing Committee

N. BAROIU (Romania) – Co-Chairman  
V. G. TEODOR (Romania)  
G. R. FRUMUSANU (Romania)  
V. MARINESCU (Romania)  
C. C. RUSU (Romania)  
L. R. MISTODIE (Romania)  
L. I. SANDU (Romania)  
M. C. GHEONEA (Romania)  
C. AFTENI (Romania)  
G. A. COSTIN (Romania)

### Contact/Correspondance

„Dunarea de Jos” University of Galati,  
47 Domneasca St., 800008 Galati, Romania  
Tel. / Fax: 0040236461353  
Prof. dr. eng. Viorel PAUNOIU  
Faculty of Engineering  
E-mail: Viorel.Paunoiu@ugal.ro

## REVIEWERS LIST

**Professor A. Archenti** (Sweden)  
**Professor P. Arrazola** (Spain)  
**Professor M. Banu** (USA)  
**Associate Professor N. Baroiu** (Romania)  
**Professor I. Bondrea** (Romania)  
**Professor M. Cacho** (Spain)  
**Professor M. Chikh** (Algeria)  
**Associate Professor B. Chirita** (Romania)  
**Professor M. Chouchane** (Tunisia)  
**Professor C. Croitoru** (Romania)  
**Professor G. R. Frumusanu** (Romania)  
**Associate Professor A. Gavrus** (France)  
**Associate Professor Ghe. Gurau** (Romania)  
**Professor T. Hama** (Japan)  
**Professor M. Iordache** (Romania)  
**Professor Ž. Jakovljević** (Serbia)  
**Professor P. Kyratsis** (Greece)  
**Professor Y. Korkolis** (USA)  
**Professor L. N. López de Lacalle** (Spain)  
**Professor C. Maier** (Romania)  
**Professor C. Mironeasa** (Romania)  
**Professor D. Nedelcu** (Romania)  
**Professor C. Nicolescu** (Sweden)  
**Professor J. Ni** (USA)  
**Professor E. Nitu** (Romania)  
**Professor Ghe. Oancea** (Romania)  
**Professor V. Paunoiu** (Romania)  
**Professor M. Piška** (Czech Republic)  
**Professor G. Racz** (Romania)  
**Professor S. Radzevich** (USA)  
**Professor J. Rech** (France)  
**Professor D. Rodrigues** (Portugal)  
**Professor A. Rosochowski** (England)  
**Assistant Professor C. C. Rusu** (Romania)  
**Professor T. Savu** (Romania)  
**Professor E. Scutelnicu** (Romania)  
**Professor L. Slatineanu** (Romania)  
**Associate Professor M.D. Stanciu** (Romania)  
**Professor V. G. Teodor** (Romania)  
**Professor N. Vaxevanidis** (Greece)  
**Professor I. Voiculescu** (Romania)  
**Professor Đ. Vukelić** (Serbia)

## PARTNERS

### ORGANIZERS



*UE Fiscodi*

### UNIVERSITY PARTNERS



Wroclaw University  
of Science and Technology



KTH  
Royal Institute of Technology



University of  
Belgrade  
Faculty of  
Mechanical  
Engineering




MEDIA SUPPORT



with the support of



IRISROBOTICS



ZONA LIBERA  
GALATI



## PLENARY LECTURES

**Wednesday, September 09, 2020**

10<sup>00</sup>-12<sup>40</sup>



**Prof. Dr. Dorel BANABIC**

Technical University of Cluj-Napoca, ROMANIA

**From Micro to Macro Scale Modeling in Sheet Metal Forming**



**Prof. Dr. Dumitru NEDELCU**

Gheorghe Asachi Technical University of Iasi, ROMANIA

**Mechanical and Thermal Analyses of Biodegradable Materials for Injection Moulding and Additive Manufacturing**



**Prof. Dr. Vidosav D. MAJSTOROVIC**

University of Belgrade, SERBIA

**Cyber Manufacturing Metrology**



**Assoc. Prof. Hab. Dr. Adinel GAVRUS**

INSA Rennes, FRANCE

**Computational Framework Concerning the Formulation of Maximum Work Principle used in Plasticity, Materials Forming and Tribology as a Consequence of a Variational Optimization Problem Defined From the Constructal Law**

## PLENARY LECTURES

**Wednesday, September 09, 2020**

16<sup>00</sup>-18<sup>00</sup>




**Prof. Dr. Pedro-José ARRAZOLA**  
Mondragon University, SPAIN

**Surface Integrity of Machined Surfaces**



**Prof. Dr. Hilde Pérez GARCÍA**  
University of Leon, SPAIN

**Collaborative Robots is Smart Manufacturing**



**Prof. Dr. Jun NI**  
University of Michigan, USA

**Industrial AI and Its Applications**

## PLENARY LECTURES

**Thursday, September 10, 2020**

10<sup>00</sup>-12<sup>00</sup>



**Prof. Dr. Gabriel FRUMUSANU**  
Dunarea de Jos University of Galati, Romania

**A new approach in manufacturing process optimization: the holistic optimization**



**Prof. Dr. Andreas ARCHENTI**  
KTH Royal Institute of Technology, SWEDEN

**Precision engineering's impact on society**



**Prof. Dr. Miroslav PÍŠKA**  
Brno University of Technology, CZECH REPUBLIC

**Tribological Performance of Graphene and Graphene Oxide Films as Solid Lubricant Layers on Tool Steel Surfaces**

## PLENARY LECTURES ABSTRACTS

### INDUSTRIAL AI AND ITS APPLICATIONS

Prof. Dr. Jun NI

Shien-Ming Wu Collegiate Professor of Manufacturing Science,  
College of Engineering, The University of Michigan, USA

Honorary Dean of UM-SJTU Joint Institute

Shanghai Jiao Tong University, China

Honorary Dean of S. M. Wu School of Intelligent Engineering

South China University of Technology, China

Email: [junni@umich.edu](mailto:junni@umich.edu)

**Abstract:** Artificial intelligence (AI) techniques have been successfully applied in various social and consumer applications, such as voice and image recognitions, social media, advertisement, etc. However, AI techniques have seen limited adoption in industry, primarily due to the difficulty in obtaining adequate sets of training data that are required by various machine learning or neural networks. Furthermore, industrial applications often require guaranteed performance (e.g., speed, accuracy, and certainty). This presentation will discuss the challenges of adopting AI techniques to industrial applications, and propose a concept of industrial AI (augmented intelligence). Often, in industrial applications, there are limited training sets that are available for machine learning or artificial neural network training. However, there frequently exist engineering models derived based on the fundamental understanding of the engineering design and analysis. Furthermore, experienced operators or engineers accumulated significant knowledge or experience over their professional career. The value behind historical maintenance records should also not be overlooked. Additionally, when sensory data and algorithms are combined with the engineering models, human experience or expert knowledge, and historical records, a new paradigm of industrial AI (iAI) becomes a powerful solution to many industrial problems. Selected applications will be presented to demonstrate the value of this new iAI.

## COMPUTATIONAL FRAMEWORK CONCERNING THE FORMULATION OF MAXIMUM WORK PRINCIPLE USED IN PLASTICITY, MATERIALS FORMING AND TRIBOLOGY AS A CONSEQUENCE OF A VARIATIONAL OPTIMIZATION PROBLEM DEFINED FROM THE CONSTRUCTAL LAW

Assoc. Prof. Hab. Dr. Adinel GAVRUS INSA Rennes, LGCGM, 20 Av. des Buttes de Coesmes, 35708 Rennes, France

Email : [adinel.gavrus@insa-rennes.fr](mailto:adinel.gavrus@insa-rennes.fr)

**Abstract:** This scientific research proposes a fundamental application of the Constructal Theory developed by Prof. Adrian BEJAN of Duke University (USA) to prove on a mathematical point of view the “Principle” of Maximum Work, used by the theory of plasticity, material forming and tribology, as a consequence of the global solution defining a constrained variational optimization problem. According to the first and second law of thermodynamics, the principal law of Constructal Theory try to complete them with a quantitative prediction of the natural tendency of any finite size system to evolve towards an optimal space-time configuration minimizing the losses and the entropy generation simultaneously with a required maximum of the global entropy. In this sense, regarding a material plastic deformation characterising the forming processes, among all possible and admissible flow undergoing well-specified boundary conditions and loadings, the real one is the one who minimizes the sum of the dissipated power of volume deformation and surfaces friction. Thus, all the mechanical variables defining the real mechanical state (velocities, stresses, strain, strain rate) are those ones which minimize the total dissipated power. A variational minimization problem under a lot of defined constraints is then obtained. Using the Principle of Virtual Powers it can be shown finally that the “Principle” of Maximum Work, used particularly in metals plasticity, is obtained as a consequence of a minimization problem under constraints based on the Constructal Theory. This generalizes its application to any type of continuous media (metals, polymers, fluid, mushy state) and allows proving an equivalent form for the friction stresses occurring on contact interfaces. The convexity properties of both the plastic and the friction potential together with their normal rule properties can be also proven using the proposed mathematical framework. It is concluded that only the rheological and tribological flow laws associated with a potential become to satisfy the second thermodynamics principle completed with the constructal law. Analytical computations concerning plane and cylindrical crushing show the feasibility of the proposed minimization problem formulation to define material flow giving accurate approximate solutions. In order to valid the whole presented theory, comparisons are made using classical analyses based on the upper and

lower bound theorems (obtained as consequences of the proposed optimization variational problem), the well-known slices method and a finite element modelling (FEM). A second application concerning the anisotropic formulation of a Coulomb friction law from a quadratic convex tribologic potential will be presented to define contact evolution during rectilinear sliding of a circular pion on a plane laminated thick plate surface along different orientations.

## CYBER MANUFACTURING METROLOGY

Prof. Dr. Vidosav D. MAJSTOROVIC, University of Belgrade, Belgrade, Serbia

Email: [vidosav.majstorovic@sbb.rs](mailto:vidosav.majstorovic@sbb.rs)

**Abstract:** The Cyber Manufacturing Metrology (C2M) are based on integration of the Cyber Physical Systems (CPSs) and connection between Internet of Things (IoTs) and Cloud technology (CT). These are high-level methodologies for development of new generation manufacturing metrology systems, which are more intelligent, flexible and self-adaptable. CP2M generates Big Data, horizontally by integration (network of machines/CMMs, processes and sensors) and vertically by control (usually defined over five levels) which should be analytically processed and managed by the CP2M. In this paper was given, a detailed analysis of the current framework of development the CP2M. A brief overview of the concept CP2M research, particularly in Serbia is given as well.

## PRECISION ENGINEERING'S IMPACT ON SOCIETY

Prof. Dr. Andreas ARCHENTI,  
KTH Royal Institute of Technology in Stockholm, Sweden

Email: [archenti@kth.se](mailto:archenti@kth.se)

**Abstract:** In the 14th to the 17th century, famous artists like Michelangelo and Leonardo da Vinci created art at a unique level of precision. Their skill was owed to their ingenuity and their ability to couple engineering with art. The pursuit to shape the world of tomorrow relies on precision and dependability: To continuously improve physical characteristics; to guarantee operational performance at all time and to support the digitization of the industries which support our liberal societies.

## **TRIBOLOGICAL PERFORMANCE OF GRAPHENE AND GRAPHENE OXIDE FILMS AS SOLID LUBRICANT LAYERS ON TOOL STEEL SURFACES**

PÍŠKA, M.<sup>1</sup>, Sedláček, J.<sup>2</sup>, Foksová, V.<sup>2</sup>, Sliwková, P.<sup>1</sup>:

<sup>1</sup> Brno University of Technology, Faculty of Mechanical Engineering,  
Institute of Manufacturing Technology, 616 69 Brno, Czech Republic

<sup>2</sup>MORAVIA CANS a. s., Tovární 532, 687 71 Bojkovice, Czech Republic

E-mail: [piska@fme.vutbr.cz](mailto:piska@fme.vutbr.cz)

Some high productive processes induce a use of effective cooling and lubricating of forming and cutting tools today. Apart of various fluids, foams, oils and emulsions with EP (extreme pressures) additives some very effective means based on graphene or graphene oxide show excellent performance in solid phase. In this study, a very effective way to enhance the tribological performance of graphene layers on tool steel surfaces is studied. The solid lubricants based on graphene and graphene oxide flakes showed a very good thermal stability, low coefficient of friction; high wear resistance, and controllable thickness, if required. However, some technological conditions and topographies of surfaces for their successful applications should be made in advance as prerequisites. The research work deals with optimization of the parameters for a high productive forming of metals.



## INSTRUCTIONS FOR THE CHAIRPERSONS

Chairpersons should be present in the computer desk at least 10 min before the beginning of the session. Please check the e-program (e-Program Booklet) to confirm the schedule of your session.

A technical staff will help to solve technical problems occurring during the session and hand out the microphones in the audience during the discussions.

Please check the presence of all the speakers scheduled for your session before the beginning of the session.

You are in charge of animating the discussion following each lecture. If necessary you can skip or shorten the discussion.

If a speaker is absent, please do not advance the following talk. You must make the audience wait until the next presentation, as defined in the initial program, by suggesting a discussion of earlier presentations.

Please note that presentation time is depending in the type of the oral presentation according to:

	<b>Lecture time</b>	<b>Discussion time</b>	<b>Total time</b>
<b>Plenary lectures</b>	30 min	10 min	40 min
<b>Full papers presentation</b>	15 min	5 min	20 min

To leave the required time for discussion, you are advised to interrupt the oral presentation of any speaker who exceeds his allowed time.

All presentations are registered by organizers.

## **INSTRUCTIONS FOR ORAL PRESENTATIONS**

Please check the e-Program Booklet to confirm the schedule of your presentation.

On the e-booklet or on the website (Program Tab), you may refer to the List of Oral Presentations ordered by IDs.

Try to be in your presentation computer desk 10 minutes prior to the starting time. Please indicate your presence to the chairperson of your session. You are expected to be present for the entire time of each session.

Please note that presentation time is depending in the type of your oral presentation according to:

	<b>Lecture time</b>	<b>Discussion time</b>	<b>Total time</b>
<b>Plenary lectures</b>	30 min	10 min	40 min
<b>Full papers presentation</b>	15 min	5 min	20 min

A simple rule is to consider 1 slide equals 1 minute of presentation. For example: a full paper presentation will have around 15 slides (15min of lecture) and for plenary lecture is around 30 slides maximum (30 min of lecture).

Please respect your presentation time. If not, the chairperson is asked to interrupt your presentation at the prescribed time to leave the required time for discussion.

All presentations are registered by organizers.

## CONFERENCE PROGRAM

<b>Wednesday, 09/09/2020 – 9.30 – 10.00 – BUCHAREST TIME</b>	
<b>09:30 – 10.00</b>	<b>Opening addresses</b> <b>Prof. dr. eng. Lucian-Puiu GEORGESCU</b> <b>Rector of Dunarea de Jos University of Galati, ROMANIA</b> <b>Prof. dr. eng. Elena SCUTELNICU</b> <b>Dean of Faculty of Engineering</b> <b>Prof. dr. eng. Viorel PAUNOIU</b> <b>Chairman of NEWTECH2020 International Conference</b>

## PROGRAM OF PLENARY LECTURES

<b>Wednesday, 09/09/2020 – 10.00 – 12.40 – BUCHAREST TIME</b>	
<b>Chair: Prof. dr. eng. Eugen RUSU, Dunarea de Jos University of Galati, Romania</b>	
<b>10.00 - 10:40</b>	<b>Prof. Dr. Dorel BANABIC</b> <b>Technical University of Cluj-Napoca, ROMANIA</b> <b>From Micro to Macro Scale Modeling in Sheet Metal Forming</b>
<b>10.40 - 11:20</b>	<b>Assoc. Prof. Hab. Dr. Adinel GAVRUS</b> <b>INSA Rennes, FRANCE</b> <b>Computational Framework Concerning the Formulation of Maximum Work Principle used in Plasticity, Materials Forming and Tribology as a Consequence of a Variational Optimization Problem Defined From the Constructal Law</b>
<b>11.20 - 12:00</b>	<b>Prof. Dr. Vidosav D. MAJSTOROVIC</b> <b>University of Belgrade, SERBIA</b> <b>Cyber Manufacturing Metrology</b>
<b>12.00 - 12:40</b>	<b>Prof. Dr. Dumitru NEDELCU</b> <b>Gheorghe Asachi Technical University of Iasi, ROMANIA</b> <b>Mechanical and Thermal Analyses of Biodegradable Materials for Injection Moulding and Additive Manufacturing</b>

## PROGRAM OF PLENARY LECTURES

<b>Wednesday, 09/09/2020 – 16.00 – 18.00 – BUCHAREST TIME</b>	
<b>Chair: : Prof. dr. eng. Viorel PAUNOIU, Dunarea de Jos University of Galati, Romania</b>	
<b>16:00 – 16.40</b>	<b>Prof. Dr. Pedro-José ARRAZOLA</b> Mondragon University, SPAIN Surface Integrity of Machined Surfaces
<b>16.40 - 17.20</b>	<b>Prof. Dr. Hilde Pérez GARCÍA</b> University of Leon, SPAIN Collaborative Robots is Smart Manufacturing
<b>17.20 - 18.00</b>	<b>Prof. Dr. Jun NI</b> University of Michigan, USA Industrial AI and Its Applications

## PROGRAM OF PLENARY LECTURES

<b>Thursday, 10/09/2020 – 10.00 – 12.00 – BUCHAREST TIME</b>	
<b>Chair: Prof. dr. eng. Virgil TEODOR, Dunarea de Jos University of Galati, Romania</b>	
<b>10.00 - 10:40</b>	<b>Prof. Dr. Gabriel FRUMUSANU</b> Dunarea de Jos University of Galati, Romania A new approach in manufacturing process optimization: the holistic optimization
<b>10.40 - 11:20</b>	<b>Prof. Dr. Andreas ARCHENTI</b> KTH Royal Institute of Technology, SWEDEN Precision engineering's impact on society
<b>11.20 - 12:00</b>	<b>Prof. Dr. Miroslav PÍŠKA</b> Brno University of Technology, CZECH REPUBLIC Tribological Performance of Graphene and Graphene Oxide Films as Solid Lubricant Layers on Tool Steel Surfaces

## PROGRAM OF ORAL PRESENTATION

<b>Thursday, 10/09/2020 - 13.40 - 16.20 - BUCHAREST TIME</b> <b>Chairs:</b> <b>Prof. dr. eng. Miroslav PÍŠKA, Brno University of Technology, Czech Republic</b> <b>Prof. dr. eng. Virgil TEODOR, Dunarea de Jos University of Galati, Romania</b>			
ID	Authors	Paper title	Hour – Bucharest Time
NT01	G. Frumusanu, V. Teodor and N. Oancea	<b>Profiling of the flat-tool for manufacturing worms with circular eccentric profile by cold forming</b>	13.40-14.00
NT14	G. A. Costin, N. Baroiu, V. Teodor, V. Paunoiu and N. Oancea	<b>Tool's profiling for rotational volumetric deformation - analytical study</b>	14.00-14.20
NT10	N. M. Vaxevanidis, N. A. Fountas, I. Papantoniou and D. E. Manolakos	<b>Experimental investigation and regression modelling to improve machinability in CNC turning of CALMAX® tool steel rods</b>	14.20-14.40
NT15	A. Polzer, T. Vancura and T. Trcka	<b>Modern circle-segment end mills analysed by new developed software for processing and analysing of the cutting forces records</b>	14.40-15.00
NT28	N. Baroiu, G. A. Costin, V. Teodor and N. Oancea	<b>Algorithm for screws profiling of a trilobed compressor</b>	15.00-15.20
NT18	A. Fernández-Valdivielso, H. Gonzalez-Barrio, A. Calleja, G. Urbikain and L. N. López de Lacalle	<b>Feasibility analysis of Ceramic cutting tools for manufacturing Austempered Ductile Iron (ADI)</b>	15.20-15.40
NT02	V. Marinescu, F. Teodor, C. Maier, V. Paunoiu and A. Epureanu	<b>Choosing the optimal order within reconfigurable manufacturing systems based on the Earning Power value</b>	15.40-16.00
NT13	C. Afteni, G. R. Frumusanu, M. Afteni, and V. Paunoiu	<b>Structural Identification of the Bearing Manufacturing Process – Case-Study</b>	16.00-16.20
<b>Pause</b>			16.20-16.40

## PROGRAM OF ORAL PRESENTATION

<b>Thursday, 10/09/2020 - 16.40 – 19.00 - BUCHAREST TIME</b>			
<b>Chairs:</b>			
<b>Prof. dr. eng. Hilde PEREZ GARCÍA, University of Leon, SPAIN</b>			
<b>Prof. dr. eng. Andreas ARCHENTI, KTH Royal Institute of Technology, Sweeden</b>			
<b>ID</b>	<b>Authors</b>	<b>Paper title</b>	<b>Hour – Bucharest Time</b>
NT07	C. C. Grigoras, B. Chirita and G. Brabie	<b>A Python and Java software approach for 2.5 axes, self-adaptive stretch forming process and IoT solution</b>	16.40-17.00
NT27	Eleonora Iunusova, Károly Szipka and Andreas Archenti	<b>Condition Monitoring of Rolling Element Bearings: Benchmarking of Data-Driven Methods</b>	17.00-17.20
NT21	A. I. Marosan, G. Constantin A. Bârsan, M. Crenganis and C. Girjob	<b>Creating an ethernet communication between a Simatic S7-1200 PLC and Arduino Mega for an omnidirectional mobile platform and industrial equipment</b>	17.20-17.40
NT23	R. E. Breaz, S. G. Racz, C. E. Girjob, M. Tera and C. Biris	<b>Using open source software CNC controllers and modular multi-axis mechanical structure as integrated teaching environment for CAD/CAM/CAE training</b>	17.40-18.00
NT26	E. Gromova	<b>PLM as a sequential round of the technical revolution</b>	18.00-18.20
NT24	P. Drumea, I. C. Dumitrescu and M. Al. Hristea	<b>Conceptual solutions for digital hydraulic pumps</b>	18.20-18.40
NT29	C. C. Rusu, L.R. Mistodie and E. Scutelnicu	<b>Data-driven Decision Model Based on Machine Learning Algorithms for Welding Areas Environmental Parameters Prediction</b>	18.40-19.00

## PROGRAM OF ORAL PRESENTATION

**Friday, 11/09/2020 – 9.00 - 11.40 - BUCHAREST TIME**  
**Chairs:**  
**Prof. dr. eng. Nikolaos VAXEVANIDIS, School of Pedagogical and Technological Education (ASPETE), Greece**  
**Prof. dr. eng. Dumitru NEDELICU, Gheorghe Asachi Technical University of Iasi, Romania**

ID	Authors	Paper title	Hour – Bucharest Time
NT12	E. L. Nitu, A. C. Gavriluta, N. Belu and C. A. Gavriluta	<b>Methodology for improving production flows on an assembly line</b>	9.00-9.20
NT09	F. Mihaila	<b>Research on the optimization of stress relief holes applied in blanks used for body-in-white stamping parts with complex asymmetrical shapes</b>	9.20-9.40
NT20	M. O. Popp, G. P. Rusu, V. Oleksik and C. Biris	<b>Influence of vertical step on forces and dimensional accuracy of SPIF parts – a numerical investigation</b>	9.40-10.00
NT04	G. Nagit, O. Dodun, L. Slatineanu, M. Ripanu, A. Mihalache and A. Hrituc	<b>Influence of some process input factors on the main dimensions of the grooves generated during the ball vibroburnishing</b>	10.00-10.20
NT16	P. Fernández-Lucio, H. González-Barrio, G. Gómez-Escudero, O. Pereira, L. N. López de Lacalle and A. Rodríguez	<b>Analysis of the influence of the hydrostatic ball burnishing pressure in the surface hardness and roughness of medium carbon steels</b>	10.20-10.40
NT08	A. D. Mazurchevici, R. Popa, C. Carausu, R. Comaneci, S. N. Mazurchevici and D. Nedelcu	<b>Basic mechanical analysis of biodegradable materials</b>	10.40-11.00
NT22	A. Barsan, M. Crenganis, A. I. Marosan and A. L. Chicea	<b>Tool holder working unit used for robot-based incremental sheet forming</b>	11.00-11.20
NT03	V. Paunoiu, C. Maier, I. Iacob and V. Marinescu	<b>Numerical analysis of hydroforming process control using variable blankholder force</b>	11.20-11.40

	<b>Pause</b>	11.40-12.00
--	--------------	-------------

## PROGRAM OF ORAL PRESENTATION

<b>Friday, 11/09/2020 – 12.00 - 14.20 - BUCHAREST TIME</b>			
<b>Chairs:</b>			
<b>Prof. dr. eng. Elena SCUTELNICU, Dunarea de Jos, University of Galati, Romania</b>			
<b>Prof. dr. eng. Catalina MAIER, Dunarea de Jos, University of Galati, Romania</b>			
<b>ID</b>	<b>Authors</b>	<b>Paper title</b>	<b>Hour – Bucharest Time</b>
NT19	H. Bulea	<b>Regression Functions For Determining the Expression of Surface Roughness at Plane Grinding of Ceramic</b>	12.00-12.20
NT17	S. Sabari, I. Galvão, C. Leitão and D. M. Rodrigues	<b>Influence of aluminium alloys relative positioning on dissimilar friction stir lap welds properties</b>	12.20-12.40
NT11	M. A. Constantin, E. L. Nitu, D. M. Iordache and C. Badulescu	<b>Study on influence of technological parameters on the friction stir butt welding process of pure copper plates</b>	12.40-13.00
NT25	S. Belabend, V. Paunoiu, N. Baroiu, R. Khelif, and I. Iacob	<b>Simulation of Ball Bearings Static Structural Analysis</b>	13.00-13.20
NT05	S. N. Florescu, M. C. Gheonea, D. Mihailescu and V. Teodor	<b>Influence of marine corrosion on the roughness of MAG welded joint surfaces</b>	13.20-13.40
NT06	M. C. Gheonea, S. N. Florescu, D. Mihailescu and V. Teodor	<b>Influence of marine corrosion on the roughness of the dry hyperbaric underwater MAG welding joints</b>	13.40-14.00
NT30	S. Kartunov	<b>Selection of product and optimal capacity utilization in manufacturing. Application of methods to cover the costs as an important factor in increasing the competitiveness of firms</b>	14.00-14.20
		<b>Conference Closing</b>	14.20



## ABSTRACTS

### NT01

#### **Profiling of the flat-tool for manufacturing worms with circular eccentric profile by cold forming**

**G. R. Frumusanu, V. Teodor and N. Oancea**

“Dunărea de Jos” University of Galați, Manufacturing Engineering Department,  
Domnească Street 111, 800201 – Galați, Romania  
E-mail: gabriel.frumusanu@ugal.ro

**Abstract.** The incremental pumps are encountered in pharmaceutical and cosmetics industries. One of the most representative categories of these pumps is formed by the progressing cavity pumps. The helical surfaces with circular profile, eccentrically positioned relative to worm axis, are frequently used in their rotors construction. In this specific case, the constructive dimensions of the worms allow their manufacturing by cold forming, with flat-tools similar to screwing dies. In this paper, an analytical algorithm for profiling such flat-tool is proposed. The algorithm starts from the analytical definition of the helical cylindrical surface with constant pitch of the generated worm, and it lays on the “Minimum distance method”. The equations of the gearing surface between worm and flat-tool are found, and, based on this, the active surface of the tool is determined. A MatLab application developed for implementing the profiling algorithm is presented. The results obtained after running the application in the case of a particular generated surface are also included.

### NT02

#### **Choosing the optimal order within reconfigurable manufacturing systems based on the Earning Power value**

**V Marinescu, F Teodor, C Maier, V Paunoiu, A Epureanu**

“Dunărea de Jos” University of Galați, Faculty of Engineering, Manufacturing Engineering  
Department  
E-mail: catalina.maier@ugal.ro

**Abstract:** In this paper will be presented the method of choosing an optimal order within a Reconfigurable Manufacturing System (RMS). The reconfigurable manufacturing systems for which we perform the analysis of optimal management belong to make-to-order (MTO) production companies. These companies start the manufacturing process based on the needs of the customers. After the content of the customers orders has been known and accepted they will deliver personalized products, provided that the cost of the production is minimum. A Virtual Workshop will be created associated with each manufacturing order with well-specified requirements (DD - DeadDate, TTF - TimeToFinish, EP - Earning Power). The workshops and orders will be transposed into a Petri net based on the new created three-dimensional model RPD3D [2]. The 3D network will be used to simulate the products manufacturing included in the orders in the virtual workshops and then the optimal order that will actually be produced on RMS from several possible orders based on the evaluation of the indicator called specific profit rate "earning power" - EP will be choosen. In this paper, we aim also to calculate the EP value of the RMS, as the most important evaluation criterion, if a certain command or a combination of commands is accepted. A study case is presented.

## NT03

# Numerical analysis of hydroforming process control using variable blankholder force

V. Paunoiu<sup>1</sup>, C. Maier<sup>1</sup>, I. Iacob<sup>1</sup> and V. Marinescu<sup>1</sup>

<sup>1</sup>Dunarea de Jos University of Galati, Faculty of Engineering, 111 Domneasca Street, 800201, Galati, Romania

E-mail: catalina.maier@ugal.ro

**Abstract.** Hydroforming was developed to provide a cost effective means to produce relatively small quantities of drawn parts or parts with asymmetrical or irregular contours that are difficult to obtain by conventional stamping. This paper presents a study of hydroforming process with variable blankholder force in order to assure the parts quality. The main idea is to decompose the blankholder function of the elementary zone of the part contour corresponding to the linear and curvilinear zone. For each zone different blankholder force is applied in correlation with the hydrostatic pressure. A numerical analysis using finite element modelisation is performed considering different sets of blankholder forces and hydrostatic pressures, as process parameters. An optimum is determined in order to avoid parts defects (thickness reduction, wrinkles, fracture) for such types of parts.

## NT04

# Influence of some process input factors on the main dimensions of the grooves generated during the ball vibroburnishing

G. Nagiț, O. Dodun, L. Slătineanu, M. Rîpanu, A. Mihalache, A. Hrițuc

“Gheorghe Asachi” Technical University of Iași, Department of Machine Manufacturing Technology, Blvd. D. Mangeron, 59 A, 700050 Iași, România

E-mail: oanad@tcm.tuiasi.ro

**Abstract.** The ball vibroburnishing is a processing method based on the plastic deformation of the workpiece surface layer, as a result of a vibration movement achieved by the ball pressed with a known force on the workpiece surface. The surface obtained by ball vibroburnishing includes grooves with different directions and partially overlapped. To know better the influence exerted by the ball vibroburnishing conditions on the main dimensional characteristics of the grooves, an experimental research was designed and materialized. As the process input factors, the diameter of the ball, the force, and the workpiece rotation speed were used. The depth and width of the grooves generated by the moving balls on the workpiece surface layer were measured. By mathematical processing of the experimental results, empirical mathematical models were determined. These models highlight the intensity of the influence exerted by the ball vibroburnishing process input factors on the main dimensions of the grooves.

## NT05

### Influence of marine corrosion on the roughness of MAG welded joint surfaces

S. N. Florescu<sup>1</sup>, M. C. Gheonea<sup>2</sup>, D. Mihailescu<sup>2</sup>, V. Teodor<sup>2</sup>

<sup>1</sup>National Institute of Marine Geology and Geo-Ecology (GeoEcoMar), 23-25 Dimitrie Onciul St., 024053 Bucharest, Romania

<sup>2</sup>"Dunarea de Jos" University of Galati, Faculty of Engineering, Domneasca Street, 47, RO-800008, Galati, Romania

E-mail: marius.gheonea@ugal.ro

**Abstract.** The paper presents in the first part the behavior of EH 36 steel in mechanized MAG welding of butt-welded joints from the naval field. Further, corrosion of the marine environment is analyzed by the electrochemical method. The paper is completed with the corrosion influence on the roughness of the welded joints surfaces.

## NT06

### Influence of marine corrosion on the roughness of the dry hyperbaric underwater MAG welding joints

M. C. Gheonea<sup>1</sup>, S. N. Florescu<sup>2</sup>, D. Mihailescu<sup>1</sup> and V. Teodor<sup>1</sup>

<sup>1</sup>"Dunarea de Jos" University of Galati, Faculty of Engineering, Domneasca Street, 47, RO-800008, Galati, Romania

<sup>2</sup>National Institute of Marine Geology and Geo-Ecology (GeoEcoMar), 23-25 Dimitrie Onciul St., 024053 Bucharest, Romania

E-mail: marius.gheonea@ugal.ro

**Abstract.** The first part of the study covers the behavior of the EH 36 shipbuilding steel subjected to MAG dry hyperbaric underwater mechanized welding. Hereinafter, the authors analyze, by using the electrochemical method, the behavior of the welded joints to marine corrosion. At the end of the article, the corrosion influence on the roughness of the test bars' surfaces depending on the potentiodynamic polarization curves is approached. With the increase of pressure, these curves indicate an increase in corrosion resistance and the decrease of the roughness of the test bars' surfaces.

## NT07

### A Python and Java software approach for 2.5 axes, self-adaptive stretch forming process and IoT solution

C C Grigoraş<sup>1</sup>, B Chirita<sup>1</sup> and G Brabie<sup>1</sup>

<sup>1</sup> “Vasile Alecsandri” University of Bacău, Faculty of Engineering, Calea Mărăşeşti 157,  
600115, Bacău, Romania  
E-mail: cosmin.grigoras@ub.ro

**Abstract.** Stretch forming is a metal forming process that implies bending and stretching a sheet of metal over a die, with the sheet being plastically deformed into the desired shape. The purpose is to obtain large parts. One of the main aspects is that the metal sheet is locked into position by gripping jaws. A hydraulic ram is raised into the metal sheet, therefore increasing the tensile forces. This process is used to draw into shape materials like aluminium, magnesium, titanium alloys, stainless steel, Inconel. These materials have in common the fact that they have poor formability or the elastic spring-back has unacceptable values. Taking this into consideration, the nature of the materials along with the fact that the metal sheet can crack, due to excessive strain, we propose a self-adaptive stretch forming process. Underlining this process is the stress-strain curve, that has three inputs: force, sample section area and strain. For each of these factors, our method uses a particular approach, as in a Python-based software and Android-based IoT solution, that uses stress and strain data. Furthermore, it controls, in real-time the hydraulic press to the point at which the material is stretch close to its ultimate yield strength.

## NT08

### Basic mechanical analysis of biodegradable materials

A-D Mazurchevici<sup>1</sup>, R Popa<sup>1</sup>, C Carausu<sup>1</sup>, R Comaneci<sup>2</sup>, S-N Mazurchevici<sup>1</sup> and D Nedelcu<sup>1,3</sup>

<sup>1</sup>“Gheorghe Asachi” Technical University of Iasi, Department of Machine Manufacturing Technology, Blvd. Mangeron, No. 59A, 700050, Iasi, Romania

<sup>2</sup>“Gheorghe Asachi” Technical” University of Iasi, Department of Materials Science and Engineering, Str. Prof. Dr. Doc. D. Mangeron, No. 41, 700050, Iasi, Romania

<sup>3</sup>Academy of Romanian Scientists, Str. Ilfov, Nr. 3, Sector 5, Bucharest, Romania  
E-mail: dnedelcu@tuiasi.ro

**Abstract.** The field of polymeric materials and manufacturing technologies is constantly evolving, offering the possibility to prototype 3D products in a responsible and ecological way, thus aiming to replace on a large scale the filaments of nonbiodegradable synthetic polymers (from fossil resources) with filaments of biodegradable materials, obtained from renewable resources. The paper supports the development mentioned above and follows to characterize biodegradable materials from the mechanical behaviour point of view, tensile, bending, and impact tests. Also, the study reflects the influence of the technological parameters on the tensile test obtained results and also aims to optimize the obtained results. The studied materials were Extrudr Green-TEC Anthracite and Extrudr BDP Pearl, which according to the obtained basic mechanical results can successfully replace conventional polymers such as Flexible, HIPS, PP and other ones.

## NT09

### Research on the optimization of stress relief holes applied in blanks used for body-in-white stamping parts with complex asymmetrical shapes

F. MIHĂILĂ  
Renault Technolgie Romania  
E-mail: fmihaila@yahoo.com

**Abstract.** Increasing the degree of deformation when stamping body-in-white parts with complex asymmetrical shapes can be achieved by optimizing the discharge holes in the flange of the blank. For this purpose, the numerical simulation of the deep-drawing process with finite element is used. Considering the circular shape of the unloading hole, the expanded shape of this hole is determined using the FEM, taking into account the safety limit given by the final shape of the stamped part. To check that the deformation that occurs at the edge of the expanded hole not cause cracks in the part the area with deformations whose values exceed the permissible limit is delimited. The arc that stretches this area along the contour of the expanded hole is divided into a convenient number of equal segments. The points at the end of each segment are then translated on the edge of unloading hole by measuring the distances between these points on the expanded blank hole. Using a mathematical modelling of the allocated points on the contour of the unloading orifice, the corrected shape of this orifice is determined, which is perforated in the flat blank.

## NT10

### Experimental investigation and regression modelling to improve machinability in CNC turning of CALMAX<sup>®</sup> tool steel rods

N M Vaxevanidis<sup>1</sup>, N A Fountas<sup>1</sup>, I. Papantoniou<sup>2</sup> and D.E. Manolakos<sup>2</sup>

<sup>1</sup>Laboratory of Manufacturing Processes & Machine Tools (LMProMaT), Department of Mechanical Engineering Educators, School of Pedagogical and Technological Education (ASPETE), Amarousion GR 151 22, Greece

<sup>2</sup>School of Mechanical Engineering, National Technical University of Athens (NTUA), Zografou, GR 157 80, Greece

E-mail: vaxev@aspete.gr

**Abstract.** This paper studies the effect of cutting conditions (spindle speed - rpm; feed rate - mm/rev and depth of cut - mm) on main cutting force and surface roughness during CNC turning of the commercial tool steel CALMAX<sup>®</sup> by Uddeholm (Sweden). Experiments have been designed using the Central composite design (CCD) approach. The experimental design involved twenty base runs with eight cube points, four center points in the cube, six axial points and two center points in axial direction. Statistical analysis to examine the effect of cutting conditions on the responses of main cutting force and surface roughness included ANOVA under the scope of generating a full quadratic model for predicting the responses. Finally, a feed-forward back-propagation neural network was applied to predict the responses of cutting force and surface roughness. It was found that regression models corresponding to the responses as well as the neural network developed can efficiently explain much of the variation in terms of main cutting force and surface roughness and thereby they may be implemented to practical applications either for predicting actual machinability parameter values or for setting up objective functions to be evaluated by intelligent algorithms for process optimization.

## NT11

### Study on the influence of technological parameters on the friction stir butt welding process of pure copper plates

M. A. Constantin<sup>1</sup>, E. L. Nitu<sup>1,\*</sup>, D. M. Iordache<sup>1</sup> and C. Badulescu<sup>2</sup>

<sup>1</sup> University of Pitesti, Faculty of Mechanics and Technology, Manufacturing and Industrial Management Department, Targul din Vale Street No.1, Pitești, Romania

<sup>2</sup> ENSTA Bretagne, IRDL-UMR CNRS 6027, F-29200 Brest, France

E-mail: eduard.nitu@upit.ro

**Abstract.** Friction stir welding - FSW is a relatively new welding process, which is increasingly used in industry, due to the advantages which it has in relation to conventional processes (by melting and adhesions). The advantages of the FSW welding process (as a solid phase welding process) are all the more obvious in the case of joining copper and its alloys, because they have a high melting temperature and high thermal diffusivity. The influence of the technological parameters of the process, the tool rotational speed and the welding feed, on the temperature and the axial force, as well as on the quality of the joint surface is presented. The study shows that the stabilization of the process takes place after a certain time from the beginning of the advance stage and highlighted the major influence of the tool rotational speed on the process temperature surface defects and the roughness of the joint surface.

## NT12

### Methodology for improving production flows on an assembly line

E. L. Nitu<sup>1,\*</sup>, A. C. Gavriluta<sup>1</sup>, N. Belu<sup>1</sup> and C. A. Gavriluta<sup>1</sup>

<sup>1</sup> University of Pitesti, Faculty of Mechanics and Technology, Manufacturing and Industrial Management Department, Targul din Vale Street No.1, Pitești, Romania

E-mail: eduard.nitu@upit.ro

**Abstract.** Globalization of production and strong competition in the economic environment requires manufacturers from automotive industry to offer their customers a wide range of products, of the best quality and at lower prices. In order to achieve a competitive advantage, the automotive industry must to adapt their production systems to mass customisation, so that they can provide the variety demanded by the customers while limiting their costs and maintaining their profitability. In this context, research to increase the performance of assembly lines is increasingly numerous and use different techniques, as: layout design, mathematic modeling, dynamic simulation, Lean manufacturing etc. This paper presents a methodology for improving production flows on an assembly line, which was developed to provide the designer and manager of assembly lines in the automotive industry with a set of logically related steps and steps that would allow to achieve a high-performance assembly line. The stages and steps of this methodology consist in the use of methods from different fields, such as: layout design, modelling-simulation of production flows, labour study, lean manufacturing, and for their application different techniques and tools are used.

## NT13

### Structural Identification of the Bearing Manufacturing Process – Case-Study

C. Afteni<sup>1</sup>, G. R. Frumusanu<sup>1</sup>, M. Afteni<sup>2</sup> and V. Paunoiu<sup>1</sup>

<sup>1</sup>“Dunărea de Jos” University, Manufacturing Engineering Department, Domneasca Street 111, 800201 – Galați, Romania

<sup>2</sup>Rulmenti S.A, Barlad, Republicii Street 320, 731108 – Barlad, Romania

E-mail: cezarina.afteni@ugal.ro

**Abstract.** In the manufacturing industry, globalization, shorter life cycles of products and changing customer needs, leads to high competitive pressure on companies. In addition to product quality and variety, flexibility, shorter processing times, and high-level compliance with delivery times have become essential factors for market success through efficient, efficacious and continually manufacturing processes optimization. To be successful in a highly competitive global production environment, a company must be able to deliver products that customers request at the requested time. In this paper is developed a novel method of structural identification of the bearing manufacturing process. This method allows the structuring of its activities, at all levels involved (order acceptance, production planning, product design, processes planning, and product processing), by elaborating the tree of the specific activities. The relations between the manufacturing process stages and related information circuit are revealed and the identification of the manufacturing process variants, at the level of each manufacturing activity is performed. Following the selection of the best alternatives from each level of the manufacturing activity, the optimal technological path is obtained for taking over an order for the bearing manufacture.

## NT14

### Tool's profiling for rotational volumetric deformation - analytical study

G. A. Costin<sup>1</sup>, N. Baroiu<sup>1</sup>, V. G. Teodor<sup>1</sup>, V. Paunoiu<sup>1</sup> and N. Oancea<sup>1</sup>

<sup>1</sup> “Dunărea de Jos” University of Galați, Department of Manufacturing Engineering, Domneasca street, no. 111, Galați, Romania

E-mail: nicusor.baroiu@ugal.ro

**Abstract.** The paper develops in an analytical form an algorithm for the profiling of the active elements of the upper half-die forming which generates by means of plastic rotary volumetric deformation of the frontal teeth. The half die has the revolving axis inclined with respect to the axis of the deformed blank, which rotates around its own axis of symmetry. In the generation process, the generating half die also performs a movement of the blank. The constitutive surfaces of the tooth flanks to be generated are complex surfaces, formed of circular arcs with variable radius and disposed on a conical base surface, on the same axis with the half-die axis. Such teeth are used for front blades in the textile industry or drilling machines which performs, besides the rotational movement of the tool and an alternate rectilinear motion thereof, creating a percussion effect on the work piece. The surfaces of the upper half and the half die teeth may be regarded as reciprocal wrapping surfaces, so that the entire generation process is based on the analytical principles of surface winding. Starting from the constructive shape of the frontal tooth plate, in a classical scheme of the structure of the oscillating motion mechanism of the upper half matrix, the shape of the deformation teeth is determined based on a specific algorithm, based on the general theory of surface winding, and dedicated software products for it.

## NT15

### Modern circle-segment end mills analysed by new developed software for processing and analysing of the cutting forces records

**A. Polzer, T. Vancura and T. Trecka**

Institute of Manufacturing Technology, Faculty of Mechanical Engineering, Brno University of Technology. Technicka 2896, 616 69 Brno, Czech Republic

E-mail: polzer@fme.vutbr.cz

**Abstract.** At present, 5-axis machining is often realized with ball end mills that do not achieve the advantages of the modern circle-segment end mills. In recent studies, these tools have been compared concerning the quality of the machined surfaces, machining times and cutting forces. An essential part of the research was an analysis of the force loading of the used tools. To get accurate data about force acting during the machining process, it was necessary to undergo experimental measuring using a cutting force dynamometer. For a force records analysis, the new software was developed based on the MATLAB platform. Evaluated results obtained by the new software are presented in the paper and compared with recent studies.

## NT16

### Analysis of the influence of the hydrostatic ball burnishing pressure in the surface hardness and roughness of medium carbon steels

**P. Fernández-Lucio<sup>1</sup>, H. González-Barrío<sup>1</sup>, G. Gómez-Escudero<sup>1</sup>, O. Pereira<sup>2</sup>, L. N. López de Lacalle<sup>2</sup> and A. Rodríguez<sup>2</sup>**

<sup>1</sup> Department of Mechanical Engineering, University of the Basque Country (UPV/EHU)  
Faculty of Engineering in Bilbao, Plaza Torres de Quevedo s/n, 48013 Bilbao, Spain.

<sup>2</sup> Aeronautics Advanced Manufacturing Center, University of the Basque Country (UPV/EHU),  
Parque Tecnológico de Bizkaia, 48170 Zamudio, Spain.

E-mail: pablo.fernandezd@ehu.eus

**Abstract.** Standing sectors in the industry such as railroad or plastic injection moulds presents many challenges for manufacturing complex components in terms of finishing requirements and mechanical properties. Because of that, hydrostatic ball burnishing is considered an optimal solution since it reduces surface roughness and generate hardened surfaces and compressive residual stresses, increasing the performance and lifespan of this parts in terms of resistance and mechanical fatigue. Additionally, this technology could be integrated directly into the machining centres, what reduces times and dimensional errors arising from mooring changes. Therefore, lead times and production costs can be drastically reduced in comparison with other finishing techniques. The aim of this project is to analyse the use of the ball burnishing process to improve the final quality of medium carbon steel surfaces, minimizing surface roughness and improving hardness. In order to achieve significant results, different working pressures are analysed in terms of surface roughness and hardness in AISI 1045 and AISI P20 steels. The results showed a reduction in roughness parameters of more than 89% for both materials using a pressure of 10 MPa. Moreover, at a pressure of 30 MPa, the surface hardness has been increased by 15% and 34% respectively.



## NT17

### Influence of aluminium alloys relative positioning on dissimilar friction stir lap welds properties

S. Sabari<sup>1\*</sup>, I. Galvão<sup>1,2</sup>, C. Leitão<sup>1</sup> and D. M. Rodrigues<sup>3</sup>

<sup>1</sup> CEMMPRE, Department of Mechanical Engineering, University of Coimbra, Portugal

<sup>2</sup> ISEL, Department of Mechanical Engineering, Polytechnic Institute of Lisbon, Portugal

<sup>3</sup> ISISE, Department of Mechanical Engineering, University of Coimbra, Portugal

E-mail: sree.sabari@dem.uc.pt

**Abstract.** Very thin sheets of heat treatable (AA6082-T6) and non-heat treatable (AA5754-H22) aluminium alloys were used to produce dissimilar joints by friction stir lap welding. Joint strength and mechanical heterogeneity were assessed by performing lap tensile-shear and microhardness testing, respectively. Optical microscopy was used to analyse the weld morphology. Welding machine outputs, such as torque and axial force, were analysed in order to capture differences in the alloys strength during dissimilar welding. From the process outputs analysis, it was concluded that higher Z-Forces were necessary while positioning the AA5754 alloy at the top of lap configuration, indicating that this alloy offered higher resistance to the tool stirring than the AA6082 alloy. These results were associated with the flow softening of the AA6082 alloy during welding, which was explained using finite element analysis to illustrate the welding thermal cycles and the precipitation behaviour of this alloy. The lap welds defect formation was also related to the base materials plastic properties at high temperatures, which was inferred from process outputs data analysis. Based on the results it was shown that the lap welds defects might be suppressed by a proper positioning the dissimilar base materials in the lap joint.

## NT18

### Feasibility analysis of Ceramic cutting tools for manufacturing Austempered Ductile Iron (ADI)

A. Fernández-Valdivielso<sup>1</sup>, H. Gonzalez-Barrio<sup>2</sup>, A. Calleja<sup>2</sup>, G. Urbikain<sup>2</sup>, L. N. López de Lacalle<sup>1,2</sup>

<sup>1</sup> Aeronautics Advanced Manufacturing Center, University of the Basque Country (UPV/EHU), Parque Tecnológico de Bizkaia, 48170 Zamudio, Spain.

<sup>2</sup> Department of Mechanical Engineering, University of the Basque Country (UPV/EHU) Faculty of Engineering in Bilbao, Plaza Torres de Quevedo s/n, 48013 Bilbao, Spain.

Email: haizea.gonzalez@ehu.eus

**Abstract.** The Austempered Ductile Iron (ADI) is a ferrous cast material that presents high design flexibility, elevated resistance against weight, good tenacity, fatigue, and wear resistance, and additionally, cost-effective solution. Besides, the use of these material is found in many industrial sectors as the automotive or critical safety. However, this material presents many challenges to be manufactured in terms of low machinability compared with cast materials. The most common technique used is reducing manufacturing steps before performing the heat treatment, what it is not possible with tough dimensional requirements and complex geometries. Ceramic cutting tools are presented as a possible solution to obtain a more productive process manufacturing ADI materials. Their main characteristic consists of being hard and resistant at high temperatures but with low tenacity. Therefore, their performance is optimal applied to continuous processes as turning. This work presents a feasibility analysis of turning ADI material using ceramic inserts and a comparison with the commonly used of carbide inserts. For this purpose, an experimental campaign is performed to obtain optimal cutting parameters. Finally, cutting forces are analysed. Finally, these cutting tools perform a dry manufacturing process, aligned with an eco-friendly solution.

## NT19

# Regression Functions For Determining the Expression of Surface Roughness at Plane Grinding of Ceramic

**H. Bulea**

Transilvania University of Brasov

E-mail: [bulea@unitbv.ro](mailto:bulea@unitbv.ro)

**Abstract.** The aim of the work is to determine, through mathematical modelling using regression functions, the dependency expression between the surface roughness  $R_a$  at grinding with diamond wheels of aluminum oxide ceramic ( $Al_2O_3$ ) for plain grinding with longitudinal advance, and the values of the grinding processing.

## NT20

# Influence of vertical step on forces and dimensional accuracy of SPIF parts – a numerical investigation

**M. O. Popp<sup>1</sup>, G. P. Rusu<sup>1</sup>, V. Oleksik<sup>1</sup> and C. Biriş<sup>1</sup>**

<sup>1</sup>Lucian Blaga University of Sibiu, Department of Industrial Machinery and Equipment, Emil Cioran Street No. 4, Romania

E-mail: [gabriela.rusu@ulbsibiu.ro](mailto:gabriela.rusu@ulbsibiu.ro)

**Abstract.** Single point incremental forming (SPIF) is a new flexible sheet metal forming process characterized by low costs and the possibility to produce prototype parts without the need for a specific die. This is one of the reasons why this process is nowadays used for manufacturing of highly customized small series parts. The process involves the usage of a hemispherical punch which gradually deforms the sheet metal blank fixed by two simple clamping rings, by following a path until the final shape of the product is obtained. The aim of this paper is to investigate and analyse the influence of the vertical step over forces involved in the process and obtained geometrical accuracy, which is one of the main drawbacks for large scale implementation of the process. A numerical analysis was carried out through finite element method with different step size for frustrum pyramid shaped parts made from the same material. In this way, the most appropriate vertical step can be chosen for further experimental research in order to obtain the most accurate parts and with as little stress as possible on the equipment involved in the process.

## NT21

# Creating an ethernet communication between a Simatic S7-1200 PLC and Arduino Mega for an omnidirectional mobile platform and industrial equipment

A. I. Maroşan<sup>1</sup>, G. Constantin<sup>2</sup>, A. Bârsan<sup>1</sup>, M. Crenganiş<sup>1</sup> and C. Gîrjob<sup>1</sup>

<sup>1</sup> Lucian Blaga University of Sibiu, Engineering Faculty, 4 Emil Cioran, 550025 Sibiu, Romania

<sup>2</sup> Prof., PhD, Eng., Machines and Manufacturing Systems Department, University "Politehnica" of Bucharest, Romania

Email: adrian.marosan@ulbsibiu.ro

**Abstract.** The degree of automation in the industry increases more and more every year, trying to make equipment that collaborates less and less or not at all with the human operator. The basis of all automatic industrial equipment is PLCs. This paper presents a method of extending the number of inputs and outputs of a Siemens Simatic S7-1200 PLC, using an Arduino Mega development board, using an ethernet communication. Following the realization of this communication, the number of inputs and outputs will increase considerably, being able to connect various sensors used for the construction of an omnidirectional mobile platform, but also for equipment for industry. The advantages of using this communication are multiple both financially and in terms of flexibility and integration of robotic systems in industrial equipment.

## NT22

# Tool-holder working unit used for robot-based incremental sheet forming

A. Bârsan<sup>1</sup>, M. Crenganiş<sup>1</sup>, A. I. Maroşan<sup>1</sup> and A. L. Chicea<sup>1</sup>

<sup>1</sup> Lucian Blaga University of Sibiu, Engineering Faculty, 4 Emil Cioran, 550025 Sibiu, Romania

Email: alexandru.barsan@ulbsibiu.ro

**Abstract.** The diversity of industrial robot applications is constantly growing, and their use in manufacturing processes is increasing year by year. One of the most flexible sheet metal forming process, used mainly for rapid prototyping or small series production, is represented by the single point incremental forming (SPIF). Usually, incremental sheet forming processes are performed by means of CNC milling machines or industrial robots, both having advantages and disadvantages. Due to the superior number of axes, especially when compared with 3-axis CNC milling machines, one of the most obvious advantage of the industrial robots rely upon their superior kinematic. The approach of this paper tackles the problem of designing a tool-holder working unit for SPIF process performed through a KUKA KR 210-2 industrial robot. After designing of the working unit, and simulating the tool path, the generated program code was used afterwards to successfully control the robot to obtain a truncated cone-shape part.

## NT23

# Using open source software CNC controllers and modular multi-axis mechanical structure as integrated teaching environment for CAD/CAM/CAE training

R. E. Breaz<sup>1</sup>, S. G. Racz<sup>1</sup>, C. E. Girjob<sup>1</sup>, M. Tera<sup>1</sup> and C. Biriş<sup>1</sup>

<sup>1</sup>Lucian Blaga University of Sibiu, Faculty of Engineering, Victoriei, 10, Sibiu, 550024, Romania  
Email: radu.breaz@ulbsibiu.ro

**Abstract.** Open source CNC controllers, such as Linux CNC are used more and more because they are open source projects and consequently are available for free. Moreover, these controllers are highly customizable, and their capabilities are close to the commercial solutions. The paper presents how using Linux CNC controller and a modular structure of a multi-axis CNC machine-tools, built by a commercial company, an integrated environment for training students in implementing CAM techniques was developed. Aside the CNC controller and the machine-tool, a CAM software package was used for programming complex machining operations. The kinematic model of the machine was built, for the user to be able to simulate, in a realistic way the multi-axes machining operations. The integrated teaching environment enable the users to be trained in CNC programming for three to five axes machining operations. Advanced programming strategies, such as tool center point management (TCPM) can also be tested.

## NT24

# Conceptual solutions for digital hydraulic pumps

P. Drumea<sup>1</sup>, I. C. Dumitrescu<sup>1</sup> and M. Al. Hristea<sup>1</sup>

<sup>1</sup>INOE 2000 - Subsidiary Hydraulics and Pneumatics Research Institute, 14 Cutitul de Argint, 040558, Bucharest, Romania  
E-mail: dumitrescu.ihp@fluidas.ro

**Abstract.** One of the methods by which specialists in the field of hydraulic drives try to increase the efficiency of the systems is the use of digital hydraulics. Digital hydraulics is a system with one or more digital components that actively controls the output of the system. One of the basic elements of such a system is the digital hydraulic pump. The first proposed and recognized variant was the one with digital pumping element; from this solution, it was possible to produce digital hydraulic pumps on an industrial scale. In this article we present some solutions regarding the creation of digital hydraulic pumps starting from several fixed flow hydraulic pumps that can ensure the variation of the flow through a special selection of them. The displacement of each pump is different and chosen taking into account the binary criterion. The article gives an overview of several such systems developed within the institute.

## NT25

### Simulation of Ball Bearings Static Structural Analysis

S. Belabend<sup>1</sup>, V. Paunoiu<sup>\*2</sup>, N. Baroiu<sup>2</sup>, R. Khelif<sup>1</sup>, I. Iacob<sup>2</sup>

<sup>1</sup>“Badji Mokhtar Annaba” University of Annaba, Faculty of Engineering Science, BP 12, 23000 - Annaba, Algeria

<sup>2</sup>“Dunarea de Jos” University of Galati, Faculty of Engineering, Department of Manufacturing Engineering, 47 Domneasca St., 800008 - Galati, Romania

E-mail: b.belabend@gmail.com

**Abstract.** FEM analysis is a very efficient method for achieving results of stresses at different loading conditions according to forces and boundary conditions applied to the component from the static analysis. The purpose of the study was to collect data's using two different software and after to compare them with mathematical results. This work aims at analysing the behaviour of the ball bearings under a static load, with Solidworks, ANSYS and MESYS software. The comparison was done between the analytical results using the Hertzian theory, ANSYS and MESYS, for two different cases of loading.

## NT26

### PLM as a sequential round of the technological revolution

Elizaveta Gromova<sup>1</sup>

<sup>1</sup>Peter the Great St. Petersburg Polytechnic University, Politechnicheskaya st., 29, St. Petersburg, 195251, Russia

E-mail: lizaveta-90@yandex.ru

**Abstract.** The fourth industrial revolution is actively developing in the world. Since 2011 it has become widespread. Affecting all areas of life activity, economy, which manifests itself in the qualitative reorganization of its mechanisms, creates new adapted management models, changes the nature of production processes. The digital revolution opens up new opportunities for using digital networks, agile production systems, and new business models for all stages of production. The faster the company makes this transition, the better its chances of succeeding and outperforming its competitors. Product lifecycle management (PLM) refers to the management of data and processes used in the design, engineering, manufacturing, sales, and service of a product across its entire lifecycle. The introduction of digital technologies occurs at all stages of the product lifecycle: product development, technology development, preparation and launch of production, product production, its operation and maintenance. PLM affects the ideology of creating a new product: to reduce the time to market and save resources, the system pushes to shift the labor intensity from the "production" stage to the "design" stage. The purpose of this study is to analyze product lifecycle management in agile management and to relate it to the current state of the Russian industrial development. Theoretical and practical aspects of this concept are given. The example of PLM implementation in the Russian industrial sector is presented. The Kalashnikov concern has built a product lifecycle management system. Today, the development of production of an industrial enterprise is impossible without a clear understanding of all stages of life cycle management of the product that it produces. Summarizing, PLM is offered as a promising concept for Russian economy.

NT27

## Condition Monitoring of Rolling Element Bearings: Benchmarking of Data-Driven Methods

Eleonora Iunusova<sup>a \*</sup>, Károly Szipka<sup>a</sup>, Andreas Archenti<sup>a</sup>

<sup>a</sup> KTH Royal Institute of Technology, Sustainable Production Development / Production Engineering, Kvarnbergagatan 12, Södertälje / Brinellvägen 68, 100 44 Stockholm, Sweden  
E-mail: [iunusova@kth.se](mailto:iunusova@kth.se)

**Abstract.** Condition-based maintenance (CBM) is a maintenance strategy used to gain updated information about equipment condition and are today considered a natural part of the engineering field. The replacement of the traditional scheduled maintenance strategy in favour of CBM has the potential to significantly improve the safety of the system operating in harsh environments of the operation and increase in productivity by prolonging the life of an asset and prevent costly breakdowns. For many years CBM remained the subject of vigorous research and discussions. Increasing the level of automation and the number of sensors in industries allowed obtaining and collecting data in large amounts. The current level of computational power allows us to process and analyse this large amount of data, which has given a new leap in the development of industrial analytics. Rather than in the case of classical physics-based modelling tools, data-driven methods propose modelling and forecasting frameworks based on data analysis. Consequently, the transition to the data-driven modelling gave a leap in CBM research and has recently drawn increasing attention, providing new case studies, algorithms and results. However, technical challenges remain. Despite great flexibility and good forecasting performances there are several limitations of data-driven algorithms. This paper provides an extensive overview of the most widely used data-driven failure algorithms for rolling element bearing monitoring. Bearings have played a pivotal role for industrial machinery to operate with high efficiency and safety and they are considered to be one of the most common machine elements of precision rotating machinery e.g. actuators robot grasping, jet engines, gas and wind turbines and machine tool spindle units. An extensive benchmarking of various predictive and descriptive algorithms was performed. The analysis was carried out on a dataset from the run-to-failure experiments on bearings from NASA's Data Repository. This paper also summarizes the current trends and highlights the limitations with respect to traditional physics-based modelling. Special attention is paid in identifying research gaps and promising research directions.

## NT28

### Algorithm for screws profiling of a trilobed compressor

Nicușor Baroiu<sup>1</sup>, Georgiana Alexandra Costin<sup>1</sup>, Virgil Gabriel Teodor<sup>1</sup>,  
Nicolae Oancea<sup>1</sup>

<sup>1</sup>Dunărea de Jos University of Galați, Romania, Department of Manufacturing Engineering, Domnească street, No. 111, 800201, Galați, Romania  
E-mail: Alexandra.Costin@ugal.ro

**Abstract.** Screw compressors are characterized by high compression ratio of working fluids. Their role is to reduce the volume of working gas by increasing its pressure. The active elements of this type of compressor consist of two helical rotors, with lobes, mounted in the compressor housing. The front profile of each rotor is composed of complex curves, including, in turn, elementary curves such as arcs, linear segments, cycloidal curves and sometimes non analytic curves. The design of the front profile of the rotors is aimed at reducing the friction between the rotors and improving the sealing between their profiles during rolling. This paper presents a study of the possibility of making a conical helical rotor, multilobed, which is part of the construction of a compressor type  $Z, Z + 1$ . This type of compressor is characterized in that the number of lobes of the driven rotor is one unit higher than the number of lobes of the driving rotor. The paper proposes a profiling algorithm based on "virtual focal points theorem" as an approach to the study of the winding between the conical helical surfaces of the two rotors. The algorithm is based on the observation that the two helical surfaces form, in cross section on the axis of the driving rotor, profiles in plane gear. This allows the determining of the specific enwrapping condition and therefore the determination of one of the two profiles under the conditions in which the other profile is known. The known profile can be expressed analytically or in discrete form, obtained by measurement

## NT29

### Data-driven Decision Model Based on Machine Learning Algorithms for Welding Areas Environmental Parameters Prediction

Carmen Catalina Rusu<sup>1</sup>, Luigi Renato Mistodie<sup>1</sup>, Elena Scutelnicu<sup>1</sup>

"Dunarea de Jos" University of Galati, Faculty of Engineering,  
Department of Manufacturing Engineering  
E-mail: carmen.rusu@ugal.ro

**Abstract:** The industrial manufacturing processes are producing risk factors and potentially dangerous agents that harms directly the working operators, particularly for the case of welding engineering areas. The European Union introduced two directives, the European Council Directive 89/391/EEC and the European Parliament Directive 2012/18/, reinforced by the wider ISO 45001:2018 standard for occupational health and safety. These directives and standards provide measures to encourage improvements in the safety and health of workers and the control of major-accident hazards involving dangerous substances. However, there are many independent research projects that develops new systems for the monitoring of the industrial environmental parameters, that aim to find solutions for reducing the health risks resulting from the manufacturing processes, specifically for welding areas. In this paper, a system based on Industrial Internet of Things (IIoT) fixed and mobile sensors networks is presented, that is used for acquiring environmental data from the welding areas. The proposed solution represents a dynamic and viable way of communication, both for monitoring of the operating conditions and for the safety of workers found in hazardous environments. The interoperability of IIoT sensors and the complex real-time event monitoring, for the recognition and generation of digital industrial services, should be a prerequisite in the real-time processing and prediction of the acquired data. For achieving this goal, a data-driven decision model based on ML algorithms is proposed, that will provide prediction for the industrial environmental parameters, allowing the identification of risky situations, setting-up alarms of the personnel in case of imminent threats, and leading to a proper occupational health and safety management in welding field

## NT30

# Selection of product and optimal capacity utilization in manufacturing. Application of methods to cover the costs as an important factor in increasing the competitiveness of firms

**Stefan Kartunov**

TU of Gabrovo, BG-5300 Gabrovo, H. Dimitar Str. 4, Department MU

Email: [skartunov@abv.bg](mailto:skartunov@abv.bg)

**Abstract.** The target parameters in a manufacturing company are turnover, reduce costs and profits from the activity. Depending on the evolution of costs it can contribute to better financial results or lead to a loss so the costs cover in manufacturing is an important factor for increasing the competitiveness of firms. The article presents the Technological preparation of production (TPP) method and the simplex algorithm for obtaining the optimal results. Based on this method four examples for selecting the product and optimum capacity utilization in the production with various production costs are presented. In view of the expected profit, the most profitable deployment of the third example, second and fourth have the same potential, and the first of no interest to production based on available capacity in the company.



## PARTICIPANTS INDEX

Last Name	First Name	Organization	Country	Paper ID
<b>A</b>				
Afteni	Cezarina	Dunarea de Jos University of Galati	Romania	NT13
Afteni	Mitica	Rulmenti S.A Barlad	Romania	NT13
Archenti	Andreas	KTH Royal Institute of Technology	Sweden	KN
Arrazola	Pedro-José	Mondragon University	Spain	KN
<b>B</b>				
Badulescu	Claudiu	ENSTA Bretagne of Brest	France	NT11
Banabic	Dorel	Technical University of Cluj-Napoca	Romania	KN
Baroiu	Nicusor	Dunarea de Jos Universty of Galati	Romania	NT14, NT25, NT28
Barsan	A.	Lucian Blaga University of Sibiu	Romania	NT21, NT22
Belabend	Selma	University of Annaba	Algeria	NT25
Belu	Nadia	University of Pitesti	Romania	NT12
Biris	C.	Lucian Blaga University of Sibiu	Romania	NT20, NT23
Brabie	Gheorghe	Vasile Alecsandri University of Bacau	Romania	NT07
Breaz	Radu E	Lucian Blaga University of Sibiu	Romania	NT23
Bulea	Horatiu	Transilvania University of Brasov	Romania	NT19
<b>C</b>				
Calleja	A.	University of the Basque Country	Spain	NT18
Carausu	Constantin	Gheorghe Asachi Technical University of Iasi	Romania	NT08
Chicea	A. L.	Lucian Blaga University of Sibiu	Romania	NT22
Chirita	Bogdan	Vasile Alecsandri University of Bacau	Romania	NT07
Comaneci	Radu	Gheorghe Asachi Technical University of Iasi	Romania	NT08
Constantin	M. A.	University of Pitesti	Romania	NT11
Constantin	George	University "Politehnica" of Bucharest	Romania	NT21
Costin	Georgiana Alexandra	Dunarea de Jos Universty of Galati	Romania	NT14, NT28
Crenganis	M.	Lucian Blaga University of Sibiu	Romania	NT21, NT22
<b>D</b>				
Dodun	Oana	Gheorghe Asachi Technical University of Iasi	Romania	NT04
Drumea	P.	INOE 2000 - Subsidiary Hydraulics and Pneumatics Research Institute of Bucharest	Romania	NT24
Dumitrescu	I. C.	INOE 2000 - Subsidiary Hydraulics and Pneumatics Research Institute of Bucharest	Romania	NT24
<b>E</b>				
Epureanu	Alexandru	Dunarea de Jos University of Galati	Romania	NT02

<b>F</b>				
Fernández-Lucio	Pablo	University of the Basque Country	Spain	NT16
Fernández-Valdivielso	A.	University of the Basque Country	Spain	NT18
Florescu	Stefan Nabi	National Institute of Marine Geology and Geo-Ecology of Bucharest	Romania	NT05, NT06
Fountas	N. A.	School of Pedagogical and Technological Education (ASPETE)	Greece	NT10
Frumusanu	Gabriel Radu	Dunarea de Jos University of Galati	Romania	KN,NT01, NT13
<b>G</b>				
Galvão	I.	Polytechnic Institute of Lisbon	Portugal	NT17
García	Hilde Pérez	University of Leon	Spain	KN
Gavriluta	A. C.	University of Pitesti	Romania	NT12
Gavriluta	C. A.	University of Pitesti	Romania	NT12
Gavrus	Adinel	INSA Rennes	France	KN
Gheonea	Marius Corneliu	Dunarea de Jos University of Galati	Romania	NT05, NT06
Girjob	C.	Lucian Blaga University of Sibiu	Romania	NT21, NT23
Gómez-Escudero	G.	University of the Basque Country	Spain	NT16
González-Barrio	H.	University of the Basque Country	Spain	NT16, NT18
Grigoras	Cosmin	Vasile Alecsandri University of Bacau	Romania	NT07
Gromova	Elizaveta	Peter the Great St. Petersburg Polytechnic University	Russia	NT26
<b>H</b>				
Hristea	M. AI.	INOE 2000 - Subsidiary Hydraulics and Pneumatics Research Institute of Bucharest	Romania	NT24
Hrituc	Adelina	Gheorghe Asachi Technical University of Iasi	Romania	NT04
<b>I</b>				
Iacob	Ionel	Dunarea de Jos University of Galati	Romania	NT03, NT25
Iordache	Monica Daniela	University of Pitesti	Romania	NT11
Iunusova	Eleonora	KTH Royal Institute of Technology	Sweden	NT27
<b>K</b>				
Kartunov	Stefan	TU of Gabrovo	Bulgaria	NT30
Khelif	Rabia	University of Annaba	Algeria	NT25
<b>L</b>				
Leitão	C.	University of Coimbra	Portugal	NT17
López de Lacalle	L. N.	University of the Basque Country,	Spain	NT16, NT18
<b>M</b>				
Maier	Catalina	Dunarea de Jos University of Galati	Romania	NT02, NT03
Majstorovic	Vidosav	University of Belgrade	Serbia	KN
Manolakos	D E	National Technical University of Athens	Greece	NT10
Marinescu	Vasilica	Dunarea de Jos University of Galati	Romania	NT02, NT03
Mazurchevici	Andreu-Danut	Gheorghe Asachi Technical University of Iasi	Romania	NT08
Mazurchevici	Simona-Nicoleta	Gheorghe Asachi Technical University of Iasi	Romania	NT08

Mihaila	Florentin	Renault Technologie	Romania	NT09
Mihailescu	Danut	Dunarea de Jos University of Galati	Romania	NT05, NT06
Mihalache	Andrei	Gheorghe Asachi Technical University of Iasi	Romania	NT04
Mistodie	Luigi Renato	Dunarea de Jos University of Galati	Romania	NT29
Morosan	Adrian	Lucian Blaga University of Sibiu	Romania	NT21, NT22
<b>N</b>				
Nagit	Gheorghe	Gheorghe Asachi Technical University of Iasi	Romania	NT04
Nedelcu	Dumitru	Gheorghe Asachi Technical University of Iasi	Romania	KN, NT08
Ni	Jun	University of Michigan	USA	KN
Nitu	Eduard Laurentiu	University of Pitesti	Romania	NT11, NT12
<b>O</b>				
Oancea	Nicolae	Dunarea de Jos University of Galati	Romania	NT01, NT14, NT28
Oleksik	Valentin	Lucian Blaga University of Sibiu	Romania	NT20
<b>P</b>				
Papantoniou	I.	National Technical University of Athens	Greece	NT10
Paunoiu	Viorel	Dunarea de Jos University of Galati	Romania	NT02, NT03, NT13, NT14, NT25
Pereira	O.	University of the Basque Country	Spain	NT16
Piška	Miroslav	Brno University of Technology	Czech Republic	KN
Polzer	A.	Brno University of Technology	Czech Republic	NT15
Popa	Ramona	Gheorghe Asachi Technical University of Iasi	Romania	NT08
Popp	M. O.	Lucian Blaga University of Sibiu	Romania	NT20
<b>R</b>				
Racz	Sever Gabriel	Lucian Blaga University of Sibiu	Romania	NT23
Ripeanu	Marius	Gheorghe Asachi Technical University of Iasi	Romania	NT04
Rodrigues	D. M.	University of Coimbra	Portugal	NT17
Rodríguez	A.	University of the Basque Country	Spain	NT16
Rusu	Carmen Catalina	Dunarea de Jos University of Galati	Romania	NT29
Rusu	Gabriela	Lucian Blaga University of Sibiu	Romania	NT20
<b>S</b>				
Sabari	Sree	University of Coimbra	Portugal	NT17
Scutelnicu	Elena	Dunarea de Jos University of Galati	Romania	NT29
Slatineanu	Laurentiu	Gheorghe Asachi Technical University of Iasi	Romania	NT04
Szipka	Károly	KTH Royal Institute of Technology	Sweden	NT27
<b>T</b>				
Teodor	Virgil Gabriel	Dunarea de Jos University of Galati	Romania	NT01, NT05, NT06, NT14, NT28
Teodor	Florin	Dunarea de Jos University of Galati	Romania	NT02
Tera	M.	Lucian Blaga University of Sibiu	Romania	NT23
Trcka	T.	Brno University of Technology	Czech Republic	NT15

U				
Urbikain	G.	University of the Basque Country	Spain	NT18
V				
Vancura	T.	Brno University of Technology	Czech Republic	NT15
Vaxevanidis	Nikolaos	School of Pedagogical and Technological Education (ASPETE)	Greece	NT10